


VECTALADDER® CAGE LADDER



Use (see Assembly and use instructions NT005):

VECTALADDER® cage ladder is used for access at height to areas reserved to authorized people. With a width of 600 mm, VECTALADDER® is one of the widest of the market which provides a total user-friendliness.

Technical features:

- Material: aluminium.
- Coating: raw, anodized or powder coated (ral colours) upon request: 
- Uprights: 65x24 mm.
- Nonslip rungs: 30x30 mm crimped.
- Overall ladder width: 600 mm.
- Spacing between rungs: 280 mm.
- Standard attachment brackets: offset 205 mm Ref.: 01149.
- Adjustable attachment brackets: offset from 214 mm to 472 mm Ref.: 01151.

Associated product(s):

- Self-closing gate H: 500 mm (Ref.: 01173), H: 1100 mm (Ref.: 01128).
- Exit landing length 600 mm (Ref.: 02415), length 800 mm (Ref.: 02662), length 1000 mm (Ref.: 02663).
- Landing step length 600 mm (Ref.: 03222), length 800 mm (Ref.: 03223).
- Simple safety door (Ref.: 02770) or complete (Ref.: 02790).
- Safety half-door (Ref.: 02791).
- Safety trapdoor (Ref.: 02792).
- Joint kit ladder / guardrail (Ref.: 03008).
- Fastenings for metal deck (Ref.: 03177).
- Changing flights - right platform (Ref.: 01139).
- Changing flights - left platform (Ref.: 01140).

Advantages:

- Economical.
- If available in stock, quick delivery.
- Quick and simple set-up.
- Powder coating colours of your choice upon request.
- Width of 600mm which make its access easier with equipment.

Assembly instructions (see Assembly and use instructions NT005):

- Ladder assembly by splicing kits (provided).
- Safety bows assembly by fixing clips (provided).
- Stainless steel fastenings (provided).
- Ladders in standard lengths: 3080 mm, 4200 mm, 5040 mm, 5880 mm, nestable and adjustable.
- Safety bows standard L: 1120 mm, 1400 mm, 1960 mm.

